W-HL060

High Lift capacity Diesel fuel cleaning system.

Up to 70lit/min fuel polishing system, nominal flow rate 60lit/min, cleaning fuel to 2 micron absolute, removing both free and emulsified water, bacteria and particulate

- Advanced, high speed AC system, providing full control system and monitoring
- Manual, Automatic (timer) and BMS control system
- Unique easy-priming system
- Integrated Fuel Flow Indicator
- Recirculation or transfer action
- 99.9 % free water removal in a single pass
- 99 % emulsified water removal in a single pass
- 2 micron final polish/fuel cleaning
- Tank sizes up to 125000 litres



W-HL060W-220 Base Model (wall mounted)

| Max flow rate | 70 lit/min (18.5 US gal/min) |
|------------------------|--|
| Recommended tank size | Up to 125,000 litres (33,000 US gallons) |
| Finish options | IP55 Wall mounted, Frame Mounted, Enclosure |
| Particulate removal to | 2 Micron |
| Control unit | Touch screen control |
| BMS** outputs | 6 |
| BMS** inputs | 2 |
| Power options | 220v 50hz 1ph AC / 110v 690hz 1ph AC available |
| Fuse | 3a |
| Typical current | 1a |
| Suction capability | 6-7m max vertical lift, over 3m requires non-return valve fitted |
| Port sizes | 1.5" BSP-P / NPT |
| Pump body | Steel |
| Pump type | Sliding Vane |
| Shaft | 316 Stainless steel |
| Seal | Viton/FKM |
| Dimensions * | 1000x1500x400mm (39x59x16in) |
| Weight * | 85kg est. (187lbs) |
| | |



CLEANING SPEED

Up to 70 lit/min - ideal for tank sizes up to



POWER

220vAC

110vAc (option)





Absolute Folishing (to 0.5 micron), auto biocide dosing, WASP Connect (remote control of unit), particulate counter, Auto priming pumps, auto water drains, mobile & internet connectivity, drip tray, auto change-over for multiple fuel tanks, ModBus and FieldBus options.



^{**}BMS-Building Management System



INSTALLATION

Wall Mounted, stair climbing trolley, weather-proof casing, towing unit,

frame mounted

Performance

1.5" hose, 0.5m lift, 77 lit/min

1.5" hose, 5m lift, 72 lit/min

1" hose, 3.5m lift, 62 lit/min

1" hose, 5m lift, 58 lit/min

Figures May 2020, tested with clean filter elements and 2-year-old